

ELECTROMAGNETIC DOOR HOLDERS

ANSI Standard

	GD900F	GD900W	GD900WE	GD970		GD990	
Model							
Voltage	24 VAC/DC (Special order 12 VAC/DC)	24 VAC/DC (Special order 12 VAC/DC)	24 VAC/DC (Special order 12 VAC/DC)	Dual 12/24 VDC	110 to 220 VAC	Dual 12/24 VDC	110 to 220 VAC
Holding Force (lbs)	80	80	80	32.9	38.8	32.9	38.8
Manual Release Button	Yes	No	Yes	No		No	
Mount	Floor	Flush Wall	Flush Wall	Flush Wall		Flush Wall	
Finish	Black	Stainless steel	Stainless steel	Silver		Stainless steel	
LED	No	No	Yes	No		No	
Armature Plate Type	Swivel	Swivel	Swivel	Swivel		Swivel	
Extention Rod Application	Yes	Yes	Yes	No		No	
Surface Mount Option	—	GD900WS	Optional back box SMB-050	GD970S		GD990S	
UL Certifications	UL 228, ULC C228	UL 228, ULC C228	—	UL 228, ULC C228		UL 228, ULC C228	

ELECTROMAGNETIC DOOR HOLDERS

	European Standard				Euro Standard High Security
Model	GD640S	GD840S	GD850F	GD860S	RM90
					
Voltage(VDC)	24 (Special order 12 VDC)	24 (Special order 12 VDC)	24 (Special order 12 VDC)	24 (Special order 12 VDC)	24 or dual 12/24 (Special order 12 VDC)
Holding Force (lbs)	70	80	80	80	550
Manual Release Button	Yes	Yes	Yes	Yes	No
Mount	Flush Wall	Surface Wall	Floor	Surface Wall	Surface Wall
Finish	Stainless steel	Black	Black	White	White
LED	Yes	Yes	Yes	Yes	No
Armature Plate Type	Swivel	Swivel/Self-adjustable	Swivel/Self-adjustable	Swivel/Self-adjustable	Fixed
Extention Rod Application	Yes	No	No	No	No
Bond Sensor Option	No	No	No	No	Yes