

# ELECTROMECHANICAL LOCKING DEVICES

## Electric Locks

For Narrow Stile Doors				
	ML-210N-SW	ML-300-SW	ML-350M	ML-360M
Model				
Voltage	12 to 24 VDC/AC	12 to 24 VDC/AC	12 VDC, 24 VDC	12 VDC, 24 VDC
Monitoring	Lock status	Lock status	Lock status, Door status	Lock status, Door status
Installation Direction	Horizontal, Vertical	Vertical	Horizontal, Vertical	Horizontal, Vertical
Lock Mode	Reversible Fail-Safe/Fail-Secure	Reversible Fail-Safe/Fail-Secure	Fail-Safe	Fail-Safe
Preload Capability	—	—	500 lbs (227 kg)	500 lbs (227 kg)
Standards & Compliance	—	—	BS EN 14846 Fire tested to BSEN 1634-1: 2014 & BSEN 1363-1: 2012	BS EN 14846
Optional Mechanical Override	No	Yes (Optional cylinders & keys available)	No	No
Optional Model	—	—	ML-350 (24 VDC input, Non-monitored, NF S 61-937 compliant)	ML-360 (24 VDC input, Non-monitored, NF S 61-937 compliant)
Dimensions (mm)	210 L x 25 W x 44 D	250 L x 25 W x 44 D Backset: 30	200 L x 25 W x 39.5 D	200 L x 30.5 W x 45 D

# ELECTROMECHANICAL LOCKING DEVICES

## Electromechanical Push Bar

Preload Panic Exit Device		
<b>Model</b>	<b>PBH-350</b> 	
<b>Voltage</b>	12 or 24 VDC	
<b>Static Strength</b>	1,500 lbs (680kg)	
<b>Preload Capability</b>	500 lbs (227kg)	
<b>Lock Mode</b>	Fail-Safe	
<b>Housing</b>	Aluminum anodized	
<b>Dimensions</b>	<b>Bar</b>	35 1/16" x 2 5/8" x 2 7/16" (890 x 66 x 61.5 mm)
	<b>Strike</b>	2 15/16" x 1 3/16" x 1 1/16" (75 x 30 x 17 mm)
<b>Delayed Egress Function</b>	<b>Model</b>	PBH-350DE
	<b>Buzzer Alarm</b>	95 dB
	<b>Nuisance Delay</b>	Field selectable 0, 1, 2, 3 seconds
	<b>Exit Delay</b>	Field selectable 15/30 seconds
<b>Functional Inputs</b>	Emergency signal input Door ajar input	

## Electromechanical Mortise Lock

ANSI Standard Mortise Lock	
<b>Model</b>	<b>GML-800</b> 
<b>Voltage</b>	Field selectable 12/24 VDC
<b>Current</b>	600mA/12VDC, 300mA/24VDC
<b>Backset</b>	2 3/4" (70 mm)
<b>Strike</b>	4 7/8" x 1 1/4" (123.8 x 31.75 mm), furnished with dust box
<b>Finish</b>	Brushed stainless steel (US32D)
<b>Lock Mode</b>	Field changeable fail-safe/fail-secure
<b>Handing</b>	Reversible latchbolt for right and left hand doors
<b>Optional Monitoring Outputs</b>	Lock status, Request-to-Exit/Enter (Lever rotation), Door status
<b>Optional Accessories</b>	Cylinder, Keys, Lever sets