

# E-ACCESS

## Bluetooth Access Control Proximity Readers

E1196 / Easiprox+ / DG-360+ Series



Easiprox<sup>+</sup>

**Access Control Proximity Reader**

4 1/2" x 3 1/8" x 11/16"  
(114 x 80 x 18 mm)  
Navy blue finish



Easiprox Slim<sup>+</sup>

**Access Control Proximity Reader**

3 7/16" x 1 3/4" x 15/16"  
(88 x 44 x 23 mm)  
Black finish



E1196

**Access Control Reader**

4 1/2" x 2 3/4" x 1 3/16"  
(114 x 69.5 x 30 mm)  
Black/White finish



DG-360<sup>+</sup>

**Access Control Proximity Reader**

3 3/8" x 3 3/8" x 13/16"  
(86 x 86 x 20 mm)  
Black finish

*European standard size*



DG-365<sup>+</sup>

**Access Control Proximity Reader**

4 3/4" x 3" x 13/16"  
(120 x 76 x 21 mm)  
Chrome plated front trim

*Logo LED indicator*

### Standard Features

- Allows smartphone-operated access
- Bluetooth operating range up to 50 meters
- Adjustable Auto proximity range for convenient access
- E-Access app available for easy access control and user management
- LED and built-buzzer indicate status
- 125KHz RFID technology- using EM or EM compatible cards (except model E1196)

## Bluetooth Access Control Proximity Readers

Model	E1196	Easiprox <sup>+</sup> Easiprox Slim <sup>+</sup>	DG-360 <sup>+</sup> DG-365 <sup>+</sup>
<b>Technical Data and Functions</b>			
Voltage (VDC)	12 to 24	12	12 to 24
Bluetooth Module	BLE 4.0	BLE 4.2	BLE 4.2
Administrator/Users	1/196	1/200	1/200
Access Modes	Smartphone	Smartphone Prox card	Smartphone Prox card
RFID Prox Card Read Range	-	5 cm	3 cm
Interface	REX & Door sensor input	REX & Door sensor input, Alarm output	REX & Door sensor input, Alarm output
Tamper Alarm	-	●	●
Door Held Open Alarm (Built-in 85 dB buzzer)	●	●	-
MOSFET Relay (Prevents electromagnetic interference)	-	-	●
Anti-tailgate Function	●	-	●
<b>E-Access App Functions</b>			
Lock Action	Keep unlocked/locked status or set relock time	Keep unlocked / locked status or set relock time	Keep unlocked/locked status or set relock time
User Management	Grant or disable user access and manage user data	Add/Delete/View user data, grant user access for specific dates or time periods and change user passcode	Add/Delete/View user data, grant user access for specific dates or time periods and change user passcode
Audit Trail Events	-	1000	1000
Backup/Restore Data	●	●	●

### Warranty

The product is warranted against defects in material and workmanship while used in normal service for a period of 1 year from the date of sale to the original client. The GEM policy is one of continual development and improvement; therefore GEM reserves the right to change specifications without notice.

E-ACCESS

# Bluetooth Access Control Proximity Keypads

Illuminated Proximity Keypads with Integrated Bluetooth



**DG-170<sup>+</sup>**  
Access Control Proximity Reader/Keypad



**DG-800<sup>+</sup>**  
Access Control Proximity Reader/Keypad



**DG-320BLE**  
Access Control Proximity Readers



**DG-325BLE**  
Access Control Proximity Readers

## Standard Features

- Allows smartphone-operated access
- Bluetooth operating range up to 50 meters
- Adjustable Auto proximity range for convenient access
- E-Access app available for easy access control and user management
- LED and built-buzzer indicate status
- 125KHz RFID technology- using EM or EM compatible cards
- Keypad backlighting
- Easy data backup and restore function
- Wrong code lockout



GIANNI INDUSTRIES, INC.

Tel: +886-2-2267-7986 Fax: +886-2-2267-9876  
www.gianni.com.tw inquiry1@gianni.com.tw

## Specifications



Voltage	12VDC /24 VDC			
Bluetooth Module	BLE 4.2 Bluetooth Low Energy			
Administrator/Users	1/200			
Access Modes	Smartphone RFID prox card PIN code (4 to 8 digits)			
Interface	REX & Door sensor input Alarm output			
Internal Alarm (85 dB)	Tamper buzzer Door held open alarm			
Lock Action	Keep unlocked/locked status or set relock time			
User Management	Add/Delete/View user data Grant user access for specific dates or time periods Change user passcode			
Audit Trail Events	1000			
Mounting Style	Mullion (DG-170+) Wall switch(DG-800+)			
Read Range (125 KHz proximity)	3.5 cm for RFID cards			
Dimensions	6" x 1 3/4" x 15/16" (152 x 45 x 23 mm)	4 13/16" x 3 1/8" x15/16" (123 x 79 x 23mm)	4 1/2" x 2 3/4" x 1 9/16" (114 x 70 x 40 mm)	4 1/2" x 2 3/4" x 1 9/16" (114 x 70 x 40 mm)
Material	Chrome/Gold finish	Chrome/Gold finish IP rated weatherproof	ABS	ABS