

Door Control Modules

Useful Gadgets

Item	Model	Specifications
	ILM-300 Three-Door Interlocking Relay Module	<ul style="list-style-type: none"> ◆ Input Voltage 12 or 24VDC ◆ Relay Rating: 3A@120VAC/30VDC ◆ Dimensions: 73(L) x 63(W) mm
	ILM-200 Two-Door Interlocking Relay Module	<ul style="list-style-type: none"> ◆ Input Voltage 12VDC ◆ Relay Rating: 3A@120VAC,24VDC ◆ Dimensions: 73(L) x 63(W) mm
	DBR-200 Relay Module	<ul style="list-style-type: none"> ◆ Input Voltage: 12~24 VAC/DC ◆ Current Draw: 50mA/12VDC ◆ Relay Rating: 5A/250VAC , 5A/24VDC
	DBR-200-JP Relay Module	<ul style="list-style-type: none"> ◆ Input Voltage: 12~24 VAC/DC ◆ Current Draw: 50mA/12VDC ◆ Relay Rating: 5A/250VAC , 5A/24VDC
	FFP-1224-7A Fire Alarm Relay Module (Supports fail-safe/fail-secure devices)	<ul style="list-style-type: none"> ◆ Input Voltage: 12~24VDC ◆ Output Voltage: 12~24VDC ◆ Relay Rating: 7A/30VDC
	GPD-3015-PLUS Voltage Distribution Board	<ul style="list-style-type: none"> ◆ DC voltage averagely distributed to five output contacts ◆ Each contact with "PPTC" re-settable fuse protection based on the dynamic equilibrium of energy. ◆ Dimensions: 70 (L) x 60 (W) mm

Warranty

The product is warranted against defects in material and workmanship while used in normal service for a period of 1 year from the date of sale to the original customer. The GEM policy is one of continual development and improvement; therefore GEM reserves the right to change specifications without notice.